

200 SERIES LOW PRESSURE DIAPHRAGM (WATER COLUMN) GAUGE ACCESSORIES

300 SERIES BRASS CASE LIQUID FILLED GAUGE ACCESSORIES†

• = Option/accessory is available

C = Consult factory for availability

STD = Standard stock model specification

MODEL NO.	25-200	25-210	25-224	40-200
CONNECTION				
Black Rear Flange (BLRF)	•			
304SS Rear Flange (SSRF)				•
Black Front Flange (BLFF)	•	•		•
304SS Front Flange (SSFF)				•
Chrome Front Flange (CFF)	•	•		
Stainless Steel Case (SSC)	•	•		STD
Glass Lens (GL)*	•	•		•
Safety Glass Lens (SGL)*	•	•		•
Plexiglass™ Lens (PL)	STD	STD		•
Recalibrator Lens (RL)	•	•		
Red Set Pointer (SP)	•	•	•	•
Maximum Indicating Pointer (MIP)	•	•	•	C
Overpressure Protection (OP)	C	C	C	C
SS Bezel w/U-Clamp (SSB-U)		•		
Black Bezel w/U-Clamp (BB-U)		•		
Black Cover Ring (BCR)	•	•		
Stainless Steel Cover Ring (SSCR)	•	•		STD
Chrome Cover Ring (CCR)	•	•		
Laser Marking (LM)	•	•	•	•
Stainless Steel Tagging (ST)	•	•	•	•
Orifice - Brass Press Fit - 0.3mm (BP3)		•	•	•
Orifice - Brass Threaded - 0.3mm (BT3)	•	•	•	•

STANDARD ORIFICE FOR 200 SERIES GAUGE IS 0.3 MM PRESS FIT, UNLESS OTHERWISE SPECIFIED.

* A steel, stainless or chrome cover ring must be additionally ordered when lenses other than Plexiglass™ are utilized on all 200 Series models

Consult factory for additional non-stock and special accessory availability.

• = Option/accessory is available

CONNECTION				
Chrome Front Flange (CFF)	•	•	•	•
Chrome Front Flange (CFF) w/o Holes	•	•	•	•
Brass Front Flange (BFF)	•	•	•	•
Black Front Flange (BLFF)			•	•
304SS Rear Flange (SSRF)			•	•
Brass Rear Flange (BRF)	•	•		
Chrome Cover Ring (CCR)	•	•	•	
Chrome Bezel w/U-Clamp (CB-U)		•		•
Maximum Indicating Pointer (MIP)	•	•		
Lexan Lens (LL)			•	•
Glass Lens Overlay (GLO)	•	•		
Safety Glass Overlay (SGO)	•	•	•	•
Adapter Ring (AR)		•		•
7/16" - 20 Straight Thread*	•	•	•	•
Laser Marking (LM)	•	•	•	•
Stainless Steel Tagging (ST)	•	•	•	•
Orifice - Brass Threaded- 0.3mm (BT3)	•	•	•	•
Orifice - Brass Threaded - 0.4mm (BT4)	•	•	•	•
Orifice - Brass Threaded - 0.8mm (BT8)	•	•	•	•

STANDARD ORIFICE FOR 300 SERIES GAUGE IS 0.8 MM THREADED, UNLESS OTHERWISE SPECIFIED.

† See 300 Series Gauge Prices for any minimum quantities that may apply when ordering these accessories.

* Includes Viton® O-Ring. Consult factory for availability. Viton® is a registered trademark of DuPont Dow Elastomers.

Consult factory for additional non-stock and special accessory availability.