

Pressure Snubbers

Piston Type Snubbers

- Resist clogging and are self cleaning
- Five different sized pistons included with each snubber to ensure the correct amount of snubbing for virtually every application
- Available in brass and 316 Stainless steel in 1/4" NPT, 1/2" NPT or 7/16-20 SAE-4

Options & Accessories

Piston Type Snubbers Specifications

MODEL NO.	SIZE	MATERIAL	PRESSURE RATING
1325	1/4" NPT	Brass	6000 psi
1335	7/16-20 SAE-4	Brass	6000 psi
1350	1/2" NPT	Brass	6000 psi
5025	1/4" NPT	316 Stainless Steel	15000 psi
5050	1/2" NPT	316 Stainless Steel	15000 psi

DIMENSIONS		1/4" NPT	1/2" NPT	7/16-20 SAE-4
A	IN	0.812	1.125	0.812
	MM	20.6	28.6	20.6
B	IN	1.60	1.875	1.60
	MM	40.6	47.6	40.6
C	IN	1.04	1.25	1.24
	MM	26.4	31.8	31.5
D	IN	.56	0.625	0.36
	MM	14.2	15.9	9.1



Piston Type Snubbers

PISTON	SUGGESTED USE
A, B*	Gases
B, C	Water
C, D	Light Oil
E	Heavy Oil

* Snubber assembled and shipped with the B piston installed.

Sintered Snubbers

- Cost effective solution to protect expensive instrumentation
- Increases gauge readability by smoothing out pressure surges, pulsations and spikes
- Eliminates instrument failure due to pressure shock
- 5 basic elements available for each snubber to accommodate specific application needs
- Snubbing action achieved by utilizing a corrosion resistant 316 Stainless Steel sintered porous element
- Exotic materials or intermediate disc grades available on a per order basis
- Provides long service life with no moving parts to wear out

Options & Accessories

Sintered Snubbers Specifications

MODEL NO.	SIZE	MATERIAL	PRESSURE RATING
1125-X	1/4" NPT	Brass	6000 psi
1135-X	7/16-20 SAE-4	Brass	6000 psi
1150-X	1/2" NPT	Brass	6000 psi
5125-X	1/4" NPT	316 Stainless Steel	15000 psi
5150-X	1/2" NPT	316 Stainless Steel	15000 psi

NOTE: The "X" in the Model Number denotes the Disc option (example: 1135-C). See chart below for Disc options.

DIMENSIONS		1/4" NPT	1/2" NPT	7/16-20 SAE-4
A	IN	0.812	1.125	0.812
	MM	20.6	28.6	20.6
B	IN	1.60	1.875	1.60
	MM	40.6	47.6	40.6
C	IN	1.04	1.25	1.24
	MM	26.4	31.8	31.5
D	IN	.56	0.625	0.36
	MM	14.2	15.9	9.1



Sintered Snubbers



Sintered Snubbers Replacement Discs

Sintered Snubbers Replacement Disc Options

DISC OPTION	MODEL NO.	AVERAGE AIR FLOW ESTIMATE	SUGGESTED USE
A	PD8-A-SS1	0.25 L/MIN @ 1 psi	Gases
B	PD8-B-SS1	0.63 L/MIN @ 1 psi	Gases, Water
C	PD8-C-SS1	1.46 L/MIN @ 1 psi	Water, Light Oil
D	PD8-D-SS1	2.79 L/MIN @ 1 psi	Light Oil
E	PD8-E-SS1	3.14 L/MIN @ 1 psi	Heavy Oil