

ORDERING INFORMATION

SERIES	200							
SIZE	25	2-1/2 Inch	40	4 Inch				
CASE TYPE	200	Steel, Bottom Connection (304SS for 4")			216	ABS, Back Connection		
	206	ABS, Bottom Connection			224	ABS, Panel Mount		
	210	Steel, Back Connection			234	Gas Pressure Test Kit**		
PRESSURE RANGES	15 inH₂O Vac	-15 inH ₂ O to 0 inH ₂ O	30 inH₂O	0 inH ₂ O to 30 inH ₂ O	15 oz/in²	0 oz/in ² to 15 oz/in ²	20 oz/35 inH₂O	0 oz/in ² /inH ₂ O to 20 oz/in ² /inH ₂ O
	30 inH₂O Vac	-30 inH ₂ O to 0 inH ₂ O	60 inH₂O	0 inH ₂ O to 60 inH ₂ O	30 oz/in²	0 oz/in ² to 30 oz/in ²	32 oz/55 inH₂O	0 oz/in ² /inH ₂ O to 32 oz/in ² /inH ₂ O
	60 inH₂O Vac	-60 inH ₂ O to 0 inH ₂ O	100 inH₂O	0 inH ₂ O to 100 inH ₂ O	35 oz/in²	0 oz/in ² to 35 oz/in ²	3 psi	0 psi to 3 psi
	100 inH₂O Vac	-100 inH ₂ O to 0 inH ₂ O	160 inH₂O	0 inH ₂ O to 160 inH ₂ O	60 oz/in²	0 oz/in ² to 60 oz/in ²	5 psi	0 psi to 5 psi
	10 inH₂O	0 inH ₂ O to 10 inH ₂ O	200 inH₂O	0 inH ₂ O to 200 inH ₂ O	100 oz/in²	0 oz/in ² to 100 oz/in ²	10 psi	0 psi to 10 psi
	15 inH₂O	0 inH ₂ O to 15 inH ₂ O	10 oz/in²	0 oz/in ² to 10 oz/in ²	160 oz/in²	0 oz/in ² to 160 oz/in ²		
CONNECTION SIZE	1/4	1/4" NPT						
OPTIONS	BLRF	Black rear flange	GL	Glass lens*	OP	Over pressure protection	CCR	Chrome cover ring
	SSRF	304SS rear flange	SGL	Safety glass lens*	SSB-U	Stainless steel bezel & U-clamp	LM	Laser marking
	BLFF	Black front flange	PL	Plexiglass™ lens	BB-U	Black bezel & U-clamp	ST	Stainless steel tagging
	SSFF	304SS front flange	RL	Recalibrator lens	BCR	Black cover ring	BP3	Brass press fit orifice 0.3 mm
	CFF	Chrome front flange	SP	Red set pointer	SSCR	Stainless steel cover ring	BT3	Brass threaded orifice 0.3 mm
	SSC	Stainless steel case	MIP	Maximum indicating pointer				

Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.

NOTE: Refer to 200 Series Options & Accessories chart on page 65 for availability by model number.

* A steel, stainless or chrome cover ring must be additionally ordered when lenses other than Plexiglass™ are utilized on all 200 Series models

** Only available in 2-1/2 inch size, 20 oz/35 inH₂O