

## ORDERING INFORMATION

<b>GAUGE SIZES</b>	<b>25</b> 2-1/2"	<b>40</b> 4"					
<b>CASE TYPES</b>	<b>200</b> Steel, bottom connection (304SS for 4")		<b>216</b> ABS, back connection				
	<b>206</b> ABS, bottom connection		<b>224</b> ABS, panel mount				
	<b>210</b> Steel, back connection		<b>234</b> Gas pressure test kit**				
<b>PRESSURE RANGES</b>	<b>15 inH<sub>2</sub>O Vac</b> -15 inH <sub>2</sub> O to 0 inH <sub>2</sub> O	<b>100 inH<sub>2</sub>O</b> 0 inH <sub>2</sub> O to 100 inH <sub>2</sub> O	<b>100 oz/in<sup>2</sup></b> 0 oz/in <sup>2</sup> to 100 oz/in <sup>2</sup>	<b>60 mbar</b> 0 mbar to 60 mbar			
	<b>30 inH<sub>2</sub>O Vac</b> -30 inH <sub>2</sub> O to 0 inH <sub>2</sub> O	<b>160 inH<sub>2</sub>O</b> 0 inH <sub>2</sub> O to 160 inH <sub>2</sub> O	<b>160 oz/in<sup>2</sup></b> 0 oz/in <sup>2</sup> to 160 oz/in <sup>2</sup>	<b>100 mbar</b> 0 mbar to 100 mbar			
	<b>60 inH<sub>2</sub>O Vac</b> -60 inH <sub>2</sub> O to 0 inH <sub>2</sub> O	<b>200 inH<sub>2</sub>O</b> 0 inH <sub>2</sub> O to 200 inH <sub>2</sub> O	<b>20 oz/ in<sup>2</sup>/inH<sub>2</sub>O</b> 0 oz/in <sup>2</sup> /inH <sub>2</sub> O to 20 oz/in <sup>2</sup> /inH <sub>2</sub> O	<b>160 mbar</b> 0 mbar to 160 mbar			
	<b>100 inH<sub>2</sub>O Vac</b> -100 inH <sub>2</sub> O to 0 inH <sub>2</sub> O	<b>10 oz/in<sup>2</sup></b> 0 oz/in <sup>2</sup> to 10 oz/in <sup>2</sup>	<b>32 oz/ in<sup>2</sup>/inH<sub>2</sub>O</b> 0 oz/in <sup>2</sup> /inH <sub>2</sub> O to 32 oz/in <sup>2</sup> /inH <sub>2</sub> O	<b>250 mbar</b> 0 mbar to 250 mbar			
	<b>10 inH<sub>2</sub>O</b> 0 inH <sub>2</sub> O to 10 inH <sub>2</sub> O	<b>15 oz/in<sup>2</sup></b> 0 oz/in <sup>2</sup> to 15 oz/in <sup>2</sup>	<b>3 psi</b> 0 psi to 3 psi	<b>400 mbar</b> 0 mbar to 400 mbar			
	<b>15 inH<sub>2</sub>O</b> 0 inH <sub>2</sub> O to 15 inH <sub>2</sub> O	<b>30 oz/in<sup>2</sup></b> 0 oz/in <sup>2</sup> to 30 oz/in <sup>2</sup>	<b>5 psi</b> 0 psi to 5 psi	<b>600 mbar</b> 0 mbar to 600 mbar			
	<b>30 inH<sub>2</sub>O</b> 0 inH <sub>2</sub> O to 30 inH <sub>2</sub> O	<b>35 oz/in<sup>2</sup></b> 0 oz/in <sup>2</sup> to 35 oz/in <sup>2</sup>	<b>10 psi</b> 0 psi to 10 psi				
	<b>60 inH<sub>2</sub>O</b> 0 inH <sub>2</sub> O to 60 inH <sub>2</sub> O	<b>60 oz/in<sup>2</sup></b> 0 oz/in <sup>2</sup> to 60 oz/in <sup>2</sup>	<b>40 mbar</b> 0 mbar to 40 mbar				
<b>CONNECTION SIZE</b>	<b>1/4</b> 1/4" NPT						
<b>OPTIONS</b>	<b>BLRF</b> Black Rear Flange	<b>GL</b> Glass Lens*	<b>OP</b> Over Pressure Protection	<b>CCR</b> Chrome Cover Ring			
	<b>SSRF</b> 304SS Rear Flange	<b>SG</b> Safety Glass Lens*	<b>SSBU</b> Stainless Steel Bezel & U-Clamp	<b>LM</b> Laser Marking			
	<b>BLFF</b> Black Front Flange***	<b>PL</b> Acrylic Lens	<b>BBU</b> Black Bezel & U-Clamp	<b>ST</b> Stainless Steel Tagging			
	<b>SSFF</b> 304SS Front Flange	<b>RL</b> Recalibrator Lens	<b>BCR</b> Black Cover Ring	<b>BP3</b> Brass Press Fit Orifice 0.3 mm			
	<b>CFF</b> Chrome Front Flange***	<b>SP</b> Red Set Pointer	<b>SSCR</b> Stainless Steel Cover Ring	<b>BT3</b> Brass Threaded Orifice 0.3 mm			
	<b>SSC</b> Stainless Steel Case	<b>MIP</b> Maximum Indicating Pointer					

**Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.**

**NOTE:** Refer to 200 Series Options & Accessories chart on page 51 for availability by part number.

\* A Steel, Stainless or chrome cover ring must be additionally ordered when lenses other than acrylic are utilized on all 200 Series

\*\* Only available in 2-1/2" size, 20 oz/35 inH<sub>2</sub>O

\*\*\* Not available on 25-200 model