

	MODELS	SPECIFICATIONS
<b>Case</b>	25-200, 25-210	Black painted steel
	25-206, 25-216, 25-224	Black ABS (Acryl Nitril Butadien Styrol) with 25-224 includes zinc plated steel panel mount clamp
	40-200	304 Stainless steel
<b>Bezel</b>	40-200	304 Stainless steel
<b>Lens</b>	25-200, 25-206, 25-210, 25-216, 25-224	Clear front plexiglass
	40-200	Instrument glass
<b>Diaphragm Capsule</b>	25-200, 25-210, 25-224, 40-200	Phosphor bronze
<b>Connection</b>	25-200, 25-206, 25-210, 25-216, 25-224, 40-200	1/4" NPT brass
<b>Movement</b>	25-200, 25-210, 25-224, 40-200	Brass and Nickel-Silver with highly polished bearing surfaces
	25-206, 25-216	Cu-Alloy
<b>Accuracy</b>	25-200, 25-210, 25-224	± 1.5% Full Scale ASME grade A
	25-206, 25-216	± 2.5% Full Scale ASME grade B
	40-200	± 1% Full Scale ASME grade 1A
<b>Pointer</b>	25-200, 25-206, 25-210, 25-216, 25-224, 40-200	Black finished aluminum
<b>Dial</b>	25-200, 25-206, 25-210, 25-216, 25-224, 40-200	Aluminum, white background with black markings. Single scale except as noted in the dial configuration chart. UV resistant