

ORDERING INFORMATION

SERIES 300

SIZE **25** 2-1/2 Inch **40** 4 Inch

CASE TYPE **300** Brass, Bottom Connection **310** Brass, Back Connection

PRESSURE RANGES	30 " Vac	-30 inHg to 0	30/300	-30 inHg to 0 to 300 psi	300	0 psi to 300 psi	3000	0 psi to 3000 psi
	30/15	-30 inHg to 0 to 15 psi	15	0 psi to 15 psi	400	0 psi to 400 psi	5000	0 psi to 5000 psi
	30/30	-30 inHg to 0 to 30 psi	30	0 psi to 30 psi	600	0 psi to 600 psi	6000	0 psi to 6000 psi
	30/60	-30 inHg to 0 to 60 psi	60	0 psi to 60 psi	800	0 psi to 800 psi	7500	0 psi to 7500 psi
	30/100	-30 inHg to 0 to 100 psi	100	0 psi to 100 psi	1000	0 psi to 1000 psi	10000	0 psi to 10000 psi
	30/160	-30 inHg to 0 to 160 psi	160	0 psi to 160 psi	1500	0 psi to 1500 psi	15000	0 psi to 15000 psi
	30/200	-30 inHg to 0 to 200 psi	200	0 psi to 200 psi	2000	0 psi to 2000 psi		

SCALE OPTION **psi** psi single scale **psi/kPa** psi/kPa dual scale **psi/kg/cm²** psi/kg/cm² dual scale **psi/bar** psi/bar dual scale

CONNECTION SIZE **1/4** 1/4" NPT **1/2** 1/2" NPT **SST** 7/16-20 Adjustable

OPTIONS	CFF	Chrome front flange	BRF	Brass rear flange	LL	Lexan lens	AR	Adapter ring
	BFF	Brass front flange	CCR	Chrome cover ring	GLO	Glass lens overlay	BT3	Brass threaded orifice 0.3 mm
	BLFF	Black front flange	CB-U	Chrome bezel & u-clamp	SGO	Safety Glass overlay	BT8	Brass threaded orifice 0.8 mm
	SSRF	Stainless steel rear flange	MIP	Maximum indicating pointer				

Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.