

ORDERING INFORMATION

SERIES 600/700

SIZE **45** 4-1/2 Inch

CASE TYPE **640** Brass, Dry, Bottom Connection **660** Brass, Liquid Filled, Bottom Connection
 740 SS, Dry, Bottom Connection **760** SS, Liquid Filled, Bottom Connection

PRESSURE RANGES	30H₂O vac	-30 inH ₂ O to 0 inH ₂ O	30 " vac	-30 inHg to 0	5	0 psi to 5 psi	300	0 psi to 300 psi	5000	0 psi to 5000 psi
	60H₂O vac	-60 inH ₂ O to 0 inH ₂ O	30/15	-30 inHg to 0 to 15 psi	10	0 psi to 10 psi	400	0 psi to 400 psi	6000	0 psi to 6000 psi
	60/60H₂O	-60 inH ₂ O to 60 inH ₂ O	30/30	-30 inHg to 0 to 30 psi	15	0 psi to 15 psi	600	0 psi to 600 psi	10000	0 psi to 10000 psi
	60H₂O	0 inH ₂ O to 60 inH ₂ O	30/60	-30 inHg to 0 to 60 psi	30	0 psi to 30 psi	800	0 psi to 800 psi	15000	0 psi to 15000 psi
	100H₂O	0 inH ₂ O to 100 inH ₂ O	30/100	-30 inHg to 0 to 100 psi	60	0 psi to 60 psi	1000	0 psi to 1000 psi	20000	0 psi to 20000 psi
	160H₂O	0 inH ₂ O to 160 inH ₂ O	30/160	-30 inHg to 0 to 160 psi	100	0 psi to 100 psi	1500	0 psi to 1500 psi	30000	0 psi to 30000 psi
	200H₂O	0 inH ₂ O to 200 inH ₂ O	30/200	-30 inHg to 0 to 200 psi	160	0 psi to 160 psi	2000	0 psi to 2000 psi	40000	0 psi to 40000 psi
	300H₂O	0 inH ₂ O to 300 inH ₂ O	30/300	-30 inHg to 0 to 300 psi	200	0 psi to 200 psi	3000	0 psi to 3000 psi	60000	0 psi to 60000 psi

SCALE OPTION **H₂O** inH₂O single scale **psi** psi single scale **psi/kPa** psi/kPa dual scale **psi/kg/cm²** psi/kg/cm² dual scale **psi/bar** psi/bar dual scale

CONNECTION SIZE **1/4** 1/4" NPT **1/2** 1/2" NPT **9/16-18** 9/16-18 UNF 3B (above 30000 psi standard)

OPTIONS	SGL	Safety glass lens	CPMR	Chrome panel mount ring
	GL	Glass lens	MDM	Manocont dampened movement
	MIP	Maximum indicating pointer	OS	Overload stop
	BPMR	Black panel mount ring	BT8	Brass threaded orifice 0.8 mm

Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.