

## ORDERING INFORMATION

<b>SERIES</b>	800							
<b>SIZE</b>	60 6 Inch							
<b>CASE TYPE</b>	800 SS Case, Bottom Connection							
<b>PRESSURE RANGES</b>	<b>30 " Vac</b>	-30 inHg to 0	<b>30/300</b>	-30 inHg to 0 to 300 psi	<b>300</b>	0 psi to 300 psi	<b>5000</b>	0 psi to 5000 psi
	<b>30/15</b>	-30 inHg to 0 to 15 psi	<b>15</b>	0 psi to 15 psi	<b>400</b>	0 psi to 400 psi	<b>6000</b>	0 psi to 6000 psi
	<b>30/30</b>	-30 inHg to 0 to 30 psi	<b>30</b>	0 psi to 30 psi	<b>600</b>	0 psi to 600 psi	<b>10000</b>	0 psi to 10000 psi
	<b>30/60</b>	-30 inHg to 0 to 60 psi	<b>60</b>	0 psi to 60 psi	<b>1000</b>	0 psi to 1000 psi	<b>15000</b>	0 psi to 15000 psi
	<b>30/100</b>	-30 inHg to 0 to 100 psi	<b>100</b>	0 psi to 100 psi	<b>1500</b>	0 psi to 1500 psi	<b>20000</b>	0 psi to 20000 psi
	<b>30/160</b>	-30 inHg to 0 to 160 psi	<b>160</b>	0 psi to 160 psi	<b>2000</b>	0 psi to 2000 psi		
	<b>30/200</b>	-30 inHg to 0 to 200 psi	<b>200</b>	0 psi to 200 psi	<b>3000</b>	0 psi to 3000 psi		
<b>SCALE OPTION</b>	psi psi single scale							
<b>CONNECTION SIZE</b>	1/4 1/4" NPT		1/2 1/2" NPT (standard for 20000 psi)					
<b>OPTIONS</b>	<b>SSFF</b>	304SS front flange	<b>ST</b>	Stainless steel tagging				
	<b>SSRF</b>	304SS rear flange	<b>BP3</b>	Brass press fit orifice 0.3 mm (below 10,000 psi)				
	<b>GC</b>	Gauge carrying case	<b>BT8</b>	Brass threaded orifice 0.8 mm (below 10,000 psi)				
	<b>LM</b>	Laser marking	<b>ST8</b>	316SS threaded orifice 0.8 mm (10,000 – 20,000 psi)				