








• = Option/accessory is available

C = Consult factory for availability

STD = Standard stock model specification

MODEL NO.	15-910	25-900	25-910	25-901	25-911	40-901	40-911
CONNECTION							
Chrome Flange Ring (CFR)			•		•		
304 SS Polished Flange Ring (SSFR)			•		•		
Installed 304SS Panel Mount Clamp (SPMC)					•		
Uninstalled 304SS Panel Mount Clamp (25-459-1-55-SPMC)					•		
Installed Steel Panel Mount Clamp (PMC)			•		•		
Uninstalled Steel Panel Mount Clamp (25-459-1-PMC)			•		•		
SS Bezel w/U-Clamp (SSB-U)							•
SS Bezel (SSB)							
Adjustable Pointer (AP)						•	•
Safety Glass Lens (SGL)				•	•	•	•
Black Front Flange (BLFF)			C				
Chrome Front Flange (CFF)							
304 SS Front Flange (SSFF)					•	•	•
304 SS Rear Flange (SSRF)						•	•
Black Cover Ring (BCR)							
Chrome Cover Ring (CCR)							
304 SS Cover Ring (SSCR)						STD	STD
Maximum Indicating Pointer (MIP)				•**	•**	•	•
7/16" - 20 Straight Thread*		•	•	•	•	•	•
Laser Marking (LM)	•	•	•	•	•	•	•
Stainless Steel Tagging (ST)	•	•	•	•	•	•	•
Orifice - Brass Press Fit - 0.3mm (BP3)	•	•	•	•	•	•	•
Orifice - Brass Threaded - 0.5mm (BT5)	•	•	•	•	•		
Orifice - Brass Threaded - 0.8mm BT8)						•	•

**STANDARD ORIFICE FOR 900 SERIES GAUGE IS 0.3 MM PRESS FIT, UNLESS OTHERWISE SPECIFIED.**

\* Includes Viton® O-Ring. Consult factory for availability. Viton® is a registered trademark of DuPont Dow Elastomers.

\*\* For ranges 60 psi and above. Minimum quantities may apply when ordering this accessory for a non-stocked pressure range. Consult factory.

**Consult factory for additional non-stock and special accessory availability.**