

## ORDERING INFORMATION

<b>SERIES</b>	<b>612</b>							
<b>PRESSURE RANGES</b>	0 inH <sub>2</sub> O to 50 inH <sub>2</sub> O	<b>50 inH<sub>2</sub>O</b>	0 psig to 2 psig (4.6 ftH <sub>2</sub> O)	<b>2</b>	0 psig to 20 psig (46.2 ftH <sub>2</sub> O)	<b>20</b>	0 psig to 200 psig (461.3 ftH <sub>2</sub> O)	<b>200</b>
	0 inH <sub>2</sub> O to 100 inH <sub>2</sub> O	<b>100 inH<sub>2</sub>O</b>	0 psig to 3 psig (6.9 ftH <sub>2</sub> O)	<b>3</b>	0 psig to 25 psig (57.7 ftH <sub>2</sub> O)	<b>25</b>	0 psig to 300 psig (692.5 ftH <sub>2</sub> O)	<b>300</b>
	0 inH <sub>2</sub> O to 150 inH <sub>2</sub> O	<b>150 inH<sub>2</sub>O</b>	0 psig to 5 psig (11.5 ftH <sub>2</sub> O)	<b>5</b>	0 psig to 30 psig (69.2 ftH <sub>2</sub> O)	<b>30</b>	0 psig to 350 psig (807.9 ftH <sub>2</sub> O)	<b>350</b>
	0 inH <sub>2</sub> O to 200 inH <sub>2</sub> O	<b>200 inH<sub>2</sub>O</b>	0 psig to 10 psig (23.1 ftH <sub>2</sub> O)	<b>10</b>	0 psig to 60 psig (138.5 ftH <sub>2</sub> O)	<b>60</b>	0 psig to 500 psig (1154.2 ftH <sub>2</sub> O)	<b>500</b>
	0 inH <sub>2</sub> O to 400 inH <sub>2</sub> O	<b>400 inH<sub>2</sub>O</b>	0 psig to 15 psig (34.6 ftH <sub>2</sub> O)	<b>15</b>	0 psig to 100 psig (230.8 ftH <sub>2</sub> O)	<b>100</b>	0 psig to 750 psig (1733.3 ftH <sub>2</sub> O)	<b>750</b>
	psig = Gauge Pressure    Other ranges available on special request				0 psig to 150 psig (346.3 ftH <sub>2</sub> O)	<b>150</b>	0 psig to 1000 psig (2311.0 ftH <sub>2</sub> O)	<b>1000</b>
<b>ACCURACY</b>	<b>1</b>	± 0.25 % Full Scale (Best Fit Straight Line)			<b>2</b>	± 0.125 % Full Scale (Best Fit Straight Line)		
<b>OUTPUT SIGNALS</b>	<b>1</b>	4 mA to 20 mA, 2-wire			<b>5</b>	0 Vdc to 10 Vdc, 3-wire		
	<b>2</b>	0 Vdc to 5 Vdc, 3-wire			<b>11</b>	0.5 Vdc to 2.5 Vdc, 3-wire		
<b>PROCESS CONNECTIONS</b>	<b>N</b>	nosecone		<b>W</b>	nosecone w/added weight (1.1 lbs.)			
	<b>T</b>	G 1/2 B x 1/2 " NPT Male/1/4 " NPT Female						
<b>ELECTRICAL CONNECTIONS</b>	<b>-XX</b>	Standard Polyurethane cable						
	<b>-22-XX</b>	Optional Water-blocked PVC cable (200+ psi only)						
	<b>-38-XX</b>	Optional Teflon cable						
		<b>NOTE: XX=length of cable in feet.</b>						
<b>OPTIONS</b>	<b>PTI</b>	PT100 RTD						

**Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.**