

ORDERING INFORMATION

SERIES	612								
PRESSURE RANGES	50 inH ₂ O	0 inH ₂ O to 50 inH ₂ O	2	0 psig to 2 psig (4.6 ftH ₂ O)	20	0 psig to 20 psig (46.2 ftH ₂ O)	200	0 psig to 200 psig (461.3 ftH ₂ O)	
	100 inH ₂ O	0 inH ₂ O to 100 inH ₂ O	3	0 psig to 3 psig (6.9 ftH ₂ O)	25	0 psig to 25 psig (57.7 ftH ₂ O)	300	0 psig to 300 psig (692.5 ftH ₂ O)	
	150 inH ₂ O	0 inH ₂ O to 150 inH ₂ O	5	0 psig to 5 psig (11.5 ftH ₂ O)	30	0 psig to 30 psig (69.2 ftH ₂ O)	350	0 psig to 350 psig (807.9 ftH ₂ O)	
	200 inH ₂ O	0 inH ₂ O to 200 inH ₂ O	10	0 psig to 10 psig (23.1 ftH ₂ O)	60	0 psig to 60 psig (138.5 ftH ₂ O)	500	0 psig to 500 psig (1154.2 ftH ₂ O)	
	400 inH ₂ O	0 inH ₂ O to 400 inH ₂ O	15	0 psig to 15 psig (34.6 ftH ₂ O)	100	0 psig to 100 psig (230.8 ftH ₂ O)	750	0 psig to 750 psig (1733.3 ftH ₂ O)	
	psig = gauge pressure Other ranges available on request			150	0 psig to 150 psig (346.3 ftH ₂ O)	1000	0 psig to 1,000 psig (2311.0 ftH ₂ O)		
ACCURACIES	1	±0.25% full scale (BFSL)			2	±0.125% full scale (BFSL)			
OUTPUT SIGNALS	1	4 mA to 20 mA, 2-wire			5	0 Vdc to 10 Vdc, 3-wire			
	2	0 Vdc to 5 Vdc, 3-wire			11	0.5 Vdc to 2.5 Vdc, 3-wire			
PROCESS CONNECTIONS	N	Nosecone				W	Nosecone w/added weight (1.1 lb.)		
	T	G 1/2 B x 1/2" NPT male with 1/4" NPT female							
ELECTRICAL CONNECTIONS	XX	Standard polyurethane (PUR) cable			38-XX	Optional FEP cable			
	22-XX	Optional water-blocked PVC cable (200+ psi only)							
	NOTE: XX = length of cable in feet.								
OPTIONS	PT1	PT100 RTD *		CBC	Cable Clamp		FE	Filter Element	
	DC	Desiccant Cartridge		LP	Lightning Protection *		JB	Cable Junction Box	

Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.

* Not available for PVC cable