ORDERING INFORMATION

SERIES 627 FM and CSA approved liquid level transmitter

PRESSURE RANGES	0 inH_2O to 50 inH_2O	**50IN**	0 psig to 5 psig (11.5 ftH_2O)	**5**	0 psig to 100 psig (230.7 ftH_2O)	**100**
	0 inH_2O to 100 inH_2O	**100IN**	0 psig to 10 psig (23.1 ftH_2O)	**10**	0 psig to 160 psig (369.1 ftH_2O)	**160**
	0 inH_2O to 150 inH_2O	**150IN**	0 psig to 15 psig (34.6 ftH_2O)	**15**	0 psig to 200 psig (461.3 ftH_2O)	**200**
	0 inH_2O to 250 inH_2O	**250IN**	0 psig to 25 psig (57.7 ftH_2O)	**25**	0 psig to 300 psig (692.3 ftH_2O)	**300**
	0 inH_2O to 400 inH_2O	**400IN**	0 psig to 30 psig (69.2 ftH_2O)	**30**	0 psig to 350 psig (807.3 ftH_2O)	**350**
			0 psig to 60 psig (138.4 ftH_2O)	**60**	0 psig to 400 psig (922.7 ftH_2O)	**400**

psig = Gauge Pressure inH_2O = Inches of water ftH_2O = feet of water Other ranges available on special request

ACCURACY	**1**	±0.25 % Full Scale (Best Fit Straight Line)
	2	±0.125 % Full Scale (Best Fit Straight Line) on ≥ 4 psi only
OUTPUT SIGNALS	**1**	4 mA to 20 mA, 2-wire
PROCESS CONNECTIONS	**N**	Stainless steel nosecone **W** Stainless steel weighted nosecone (1.1 lbs.)
	T	NPT adapter, 1/2 ″ NPT male outer thread with 1/4 ″ NPT female inner thread attached to transmitter process connection with straight thread and O-ring seal
ELECTRICAL CONNECTIONS	**Specify length**	Vented polyurethane cable Other cable material available on special request

Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.