

## ORDERING INFORMATION

### SERIES 100

#### DIAL SIZE

<b>20</b>	2 Inch (Back connection only)	<b>30</b>	3 Inch
-----------	-------------------------------	-----------	--------

#### CASE TYPE

<b>100</b>	Bottom Connection	<b>110</b>	Back Connection
------------	-------------------	------------	-----------------

#### STEM LENGTH

<b>025</b>	2-1/2"	<b>060</b>	6"	<b>120</b>	12"	<b>180</b>	18"
<b>040</b>	4"	<b>090</b>	9"	<b>150</b>	15"	<b>240</b>	24"

#### TEMPERATURE RANGE

<b>-100/150</b>	-100° to 150°	<b>0/140</b>	0° to 140°	<b>20/240</b>	20° to 240°	<b>150/750</b>	150° to 750°
<b>-40/120</b>	-40° to 120°	<b>0/200</b>	0° to 200°	<b>50/300</b>	50° to 300°	<b>200/1000</b>	200° to 1000°
<b>25/125</b>	25° to 125°	<b>0/250</b>	0° to 250°	<b>50/500</b>	50° to 500°	Consult factory for additional temperature ranges	

#### SCALE OPTIONS

<b>F/C</b>	Fahrenheit/Celsius Dual Scale	<b>F</b>	Fahrenheit Single Scale <sup>1</sup>	<b>C</b>	Celsius Single Scale <sup>1</sup>	<sup>1</sup> Consult factory for available ranges
------------	-------------------------------	----------	--------------------------------------	----------	-----------------------------------	---

#### OPTIONS

<b>1/4</b>	1/4" NPT Connection (STD 2" )	<b>PL</b>	Plexiglass Lens
<b>3/8</b>	3/8" NPT Connection	<b>SG</b>	Safety Glass Lens
<b>1/2</b>	1/2" NPT Connection (STD 3" )	<b>LL</b>	Lexan Lens

**Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.**