

ORDERING INFORMATION

SERIES 300

DIAL SIZE	30	3 Inch	50	5 Inch								
CASE TYPE	300	Bottom Connection			310	Back Connection			320	Adjustable Angle Connection		
STEM LENGTH	025	2-1/2"	060	6"	120	12"	180	18"	300	30"	420	42"
	040	4"	090	9"	150	15"	240	24"	360	36"	480	48"
TEMPERATURE RANGE	-100/150	-100° to 150°		0/140	0° to 140°		20/240	20° to 240°		150/750	150° to 750°	
	-40/120	-40° to 120°		0/200	0° to 200°		50/300	50° to 300°		200/1000	200° to 1000°	
	25/125	25° to 125°		0/250	0° to 250°		50/500	50° to 500°		Consult factory for additional temperature ranges		
SCALE OPTIONS	F/C	Fahrenheit/Celsius Dual Scale		F	Fahrenheit Single Scale ¹		C	Celsius Single Scale ¹		¹ Consult factory for available ranges		
OPTIONS	1/4	1/4" NPT Connection (STD 2")		PL	Plexiglass Lens		MIP	Maximum Indicating Pointer		AU	1/2" NPT Adjustable Union	
	3/8	3/8" NPT Connection		SG	Safety Glass Lens		316	316 SS Connection & Stem		SL	Silicone Filled (500°F Max)	
	1/2	1/2" NPT Connection (STD 3")		LL	Lexan Lens		HD	Heavy Duty Stem (.375" Diameter)		MM	Manocont Movement	

Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.