

## ORDERING INFORMATION

<b>DIAL SIZES</b>	10	1" **	18	1-3/4"	20	2"
<b>CASE TYPES</b>	150	Back connection				
<b>STEM LENGTHS</b>	050	5"	120	12" †		
	080	8"	180	18" †		
<b>TEMPERATURE RANGES</b>	-100/100 F/C	-100 °F/°C to 100 °F/°C	0/250 F/C	0 °F/°C to 250 °F/°C	50/550 F/C	50 °F/°C to 550 °F/°C
	-40/160 F/C	-40 °F/°C to 160 °F/°C	20/240 F/C	20 °F/°C to 240 °F/°C	150/750 F/C	150 °F/°C to 750 °F/°C
<i>Dual Scale °F/ °C</i>	0/140 F/C	0 °F/°C to 140 °F/°C	25/125 F/C	25 °F/°C to 125 °F/°C	200/1000 F/C	200 °F/°C to 1,000 °F/°C*
<i>(Not available on 1" model)</i>	0/180 F/C	0 °F/°C to 180 °F/°C	50/300 F/C	50 °F/°C to 300 °F/°C		
	0/220 F/C	0 °F/°C to 220 °F/°C	50/400 F/C	50 °F/°C to 400 °F/°C		
<i>Single Scale °F</i>	-100/100 F	-100 °F to 100 °F	0/220 F	0 °F to 220 °F**	50/400 F	50 °F to 400 °F
	-50/120 F	-50 °F to 120 °F	0/250 F	0 °F to 250 °F	50/500 F	50 °F to 500 °F**
	-40/160 F	-40 °F to 160 °F**	20/240 F	20 °F to 240 °F	50/550 F	50 °F to 550 °F
	0/140 F	0 °F to 140 °F	25/125 F	25 °F to 125 °F**	150/750 F	150 °F to 750 °F **
	0/180 F	0 °F to 180 °F	50/250 F	50 °F to 250 °F	200/1000 F	200 °F to 1,000 °F*
	0/200 F	0 °F to 200 °F	50/300 F	50 °F to 300 °F		
<i>Single Scale °C</i>	-75/175 C	-75 °C to 175 °C	-10/110 C	-10 °C to 110 °C**	0/300 C	0 °C to 300 °C
	-50/100 C	-50 °C to 100 °C	0/50 C	0 °C to 50 °C**	0/400 C	0 °C to 400 °C
	-50/25 C	-50 °C to 25 °C	0/100 C	0 °C to 100 °C	100/400 C	100 °C to 400 °C
	-50/50 C	-50 °C to 50 °C	0/150 C	0 °C to 150 °C	100/550 C	100 °C to 550 °C*
	-40/70 C	-40 °C to 70 °C**	0/200 C	0 °C to 200 °C		
	-20/120 C	-20 °C to 120 °C	0/250 C	0 °C to 250 °C**		
	Consult factory for additional temperature ranges					
<b>OPTIONS</b>	LL	Polycarbonate Lens	PS	Pocket Sheath***	ST	Stainless Steel Tagging
	PL	Acrylic Lens †	SL	Silicone Filled (500 °F Max)†	TG	Tempered Glass Lens ††

Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.

\* Thermometers with temperature ranges 200/1000 °F and 100/500 °C are not recommended for continuous use above 800 °F/425 °C. For intermittent use only.

\*\* 1" model available only in these ranges.

\*\*\* Available for 10-150 and 18-150 models only, with stem lengths of 5" or 8".

† Available for 20-150 models only.

†† Not available on 10-150 model. Also not available with Silicone Filled (SL) option.