

## ORDERING INFORMATION

DIAL SIZES	20	2" (Back connected only)	30	3"	50	5"
CASE TYPES	300	Bottom connection	310	Back connection	320	Adjustable angle connection**
STEM LENGTHS	025	2-1/2"	120	12"	300	30"
	040	4"	150	15"	360	36"
	060	6"	180	18"	420	42"
	090	9"	240	24"	Available up to 120"	
TEMPERATURE RANGES <i>Dual Scale °F/°C</i>	-100/100 F/C	-100 °F/°C to 100 °F/°C	0/250 F/C	0 °F/°C to 250 °F/°C	50/500 F/C	50 °F/°C to 500 °F/°C
	-40/160 F/C	-40 °F/°C to 160 °F/°C	20/240 F/C	20 °F/°C to 240 °F/°C	150/750 F/C	150 °F/°C to 750 °F/°C
	0/140 F/C	0 °F/°C to 140 °F/°C	25/125 F/C	25 °F/°C to 125 °F/°C†	200/1000 F/C	200 °F/°C to 1,000 °F/°C*
	0/180 F/C	0 °F/°C to 180 °F/°C	50/300 F/C	50 °F/°C to 300 °F/°C		
	0/220 F/C	0 °F/°C to 220 °F/°C	50/400 F/C	50 °F/°C to 400 °F/°C		
<i>Single Scale °F</i>	-100/100 F	-100 °F to 100 °F	0/300 F	0 °F to 300 °F**	50/550 F	50 °F to 550 °F
	-50/120 F	-50 °F to 120 °F	0/500 F	0 °F to 500 °F**	100/800 F	100 °F to 800 °F**
	-40/160 F	-40 °F to 160 °F	20/240 F	20 °F to 240 °F	150/750 F	150 °F to 750 °F
	0/140 F	0 °F to 140 °F	25/125 F	25 °F to 125 °F	200/1000 F	200 °F to 1,000 °F*
	0/180 F	0 °F to 180 °F	50/250 F	50 °F to 250 °F		
	0/200 F	0 °F to 200 °F	50/300 F	50 °F to 300 °F		
	0/220 F	0 °F to 220 °F	50/400 F	50 °F to 400 °F		
	0/250 F	0 °F to 250 °F	50/500 F	50 °F to 500 °F		
<i>Single Scale °C</i>	-75/175 C	-75 °C to 175 °C	0/50 C	0 °C to 50 °C	0/300 C	0 °C to 300 °C
	-70/70 C	-70 °C to 70 °C**	0/60 C	0 °C to 60 °C**	0/400 C	0 °C to 400 °C
	-50/100 C	-50 °C to 100 °C**	0/80 C	0 °C to 80 °C**	0/450 C	0 °C to 450 °C
	-50/50 C	-50 °C to 50 °C	0/100 C	0 °C to 100 °C	100/400 C	100 °C to 400 °C
	-40/70 C	-40 °C to 70 °C	0/150 C	0 °C to 150 °C	100/550 C	100 °C to 550 °C*
	-20/120 C	-20 °C to 120 °C**	0/200 C	0 °C to 200 °C		
	-10/110 C	-10 °C to 110 °C**	0/250 C	0 °C to 250 °C		
		Consult factory for additional temperature ranges				
OPTIONS	6	6 mm stem diameter **	HD	Heavy-Duty Stem (0.375" Dia.)**	SG	Safety Glass Lens **
	8	8 mm stem diameter **	LL	Polycarbonate Lens	SL	Silicone Filled (500 °F Max)
	316	316 SS Connection & Stem **	MIP	Min or Max Indicating Pointer***	ST	Stainless Steel Tagging
	AU	1/2" NPT Adjustable Union**	MIP2	Min and Max Indicating Pointers***	TG	Tempered Glass Lens ††
	GD	Glow Dial †	PL	Acrylic Lens		

Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.

**Note:** All 316 Stainless Steel construction (case, bezel, wetted parts) is available. Please consult factory.

\* Thermometers with temperature ranges 200/1000 °F and 100/500 °C are not recommended for continuous use above 800 °F/425 °C. **For intermittent use only.**

\*\* Available for 3" and 5" dial sizes only.

\*\*\* Available only on 30-310 and 50-310 models.

† Available only on 50-310 and 50-320 model. Includes reflective pointer and two reflective clips.

†† Not available with Silicone Filled (SL) option.