

ORDERING INFORMATION

DIAL SIZES	10	1" **	18	1-3/4"	30	3"
	14	1-3/8" **	20	2"		
CASE TYPES	350	Back connection				
STEM LENGTHS	050	5" **	120	12"		
	080	8" **	180	18"		
TEMPERATURE RANGES	-100/100 F/C	-100 °F/°C to 100 °F/°C	0/250 F/C	0 °F/°C to 250 °F/°C	50/550 F/C	50 °F/°C to 550 °F/°C
	-40/160 F/C	-40 °F/°C to 160 °F/°C	20/240 F/C	20 °F/°C to 240 °F/°C	150/750 F/C	150 °F/°C to 750 °F/°C
<i>Dual Scale °F/°C</i>	0/140 F/C	0 °F/°C to 140 °F/°C	25/125 F/C	25 °F/°C to 125 °F/°C	200/1000 F/C	200 °F/°C to 1,000 °F/°C*
(Not available on 1" model)	0/180 F/C	0 °F/°C to 180 °F/°C	50/300 F/C	50 °F/°C to 300 °F/°C		
	0/220 F/C	0 °F/°C to 220 °F/°C	50/400 F/C	50 °F/°C to 400 °F/°C		
<i>Single Scale °F</i>	-100/100 F	-100 °F to 100 °F	0/220 F	0 °F to 220 °F**	50/400 F	50 °F to 400 °F
	-50/120 F	-50 °F to 120 °F	0/250 F	0 °F to 250 °F	50/500 F	50 °F to 500 °F**
	-40/160 F	-40 °F to 160 °F**	20/240 F	20 °F to 240 °F	50/550 F	50 °F to 550 °F
	0/140 F	0 °F to 140 °F	25/125 F	25 °F to 125 °F**	150/750 F	150 °F to 750 °F **
	0/180 F	0 °F to 180 °F	50/250 F	50 °F to 250 °F	200/1000 F	200 °F to 1,000 °F*
	0/200 F	0 °F to 200 °F	50/300 F	50 °F to 300 °F		
<i>Single Scale °C</i>	-75/175 C	-75 °C to 175 °C	0/50 C	0 °C to 50 °C**	0/300 C	0 °C to 300 °C
	-50/100 C	-50 °C to 100 °C	0/100 C	0 °C to 100 °C	0/400 C	0 °C to 400 °C
	-50/25 C	-50 °C to 25 °C	0/150 C	0 °C to 150 °C	100/400 C	100 °C to 400 °C
	-50/50 C	-50 °C to 50 °C	0/100 C	0 °C to 100 °C	100/550 C	100 °C to 550 °C*
	-40/70 C	-40 °C to 70 °C**	0/150 C	0 °C to 150 °C		
	-20/120C	-20 °C to 120 °C	0/200 C	0 °C to 200 °C		
	-10/110 C	-10 °C to 110 °C**	0/250 C	0 °C to 250 °C**		
	Consult factory for additional temperature ranges					
OPTIONS	LL	Polycarbonate Lens	PS	Pocket Sheath***	TG	Tempered Glass Lens †
	PL	Acrylic Lens	SST	Stainless Steel Tagging		

Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.

Note: All 316 Stainless Steel construction (case, bezel, wetted parts) is available. Please consult factory.

* Thermometers with temperature ranges 200/1000 °F and 100/500 °C are not recommended for continuous use above 800 °F/425 °C. For intermittent use only.

** 10-350 and 14-350 models are only available in these stem lengths and ranges.

*** Available for 5" or 8" stem lengths only.

† Not available on 10-350 model.