

## ORDERING INFORMATION

### SERIES 300

<b>PRESSURE RANGES</b>	0 psig to 15 psig	<b>15</b>	0 psig to 200 psig	<b>200</b>	0 psig to 2000 psig	<b>2000</b>	0 psia to 30 psia	<b>30A</b>
	0 psig to 30 psig	<b>30</b>	0 psig to 300 psig	<b>300</b>	0 psig to 3000 psig	<b>3000</b>	0 psia to 60 psia	<b>60A</b>
	0 psig to 60 psig	<b>60</b>	0 psig to 500 psig	<b>500</b>	0 psig to 5000 psig	<b>5000</b>	0 psia to 100 psia	<b>100A</b>
	0 psig to 100 psig	<b>100</b>	0 psig to 1000 psig	<b>1000</b>	0 psig to 10000 psig	<b>10000</b>	0 psia to 150 psia	<b>150A</b>
	0 psig to 150 psig	<b>150</b>	0 psig to 1500 psig	<b>1500</b>	0 psia to 15 psia	<b>15A</b>	0 psia to 200 psia	<b>200A</b>
							0 psia to 300 psia	<b>300A</b>

psig = Gauge Pressure

psia = Absolute Pressure

Other ranges available on special request

<b>ACCURACY</b>	<b>1</b> ±0.5 % Full Scale (Best Fit Straight Line)	<b>2</b> ±0.25 % Full Scale (Best Fit Straight Line)
-----------------	---	--

<b>OUTPUT</b>	<b>1</b> 4 mA to 20 mA, 2-wire	<b>2</b> 0 Vdc to 5 Vdc, 3-wire	<b>3</b> 1 Vdc to 5 Vdc, 3-wire	<b>5</b> 0 Vdc to 10 Vdc, 3-wire
---------------	--------------------------------	---------------------------------	---------------------------------	----------------------------------

<b>PROCESS CONNECTIONS</b>	<b>2</b> 1/4 " NPT male	<b>45</b> 7/16 " -20 UNF #4 SAE	<b>8</b> 1/2 " NPT male
----------------------------	-------------------------	---------------------------------	-------------------------

<b>ELECTRICAL CONNECTIONS</b>	<b>1</b> 36 " cable (connected to option 8)	<b>8</b> Hirschmann (DIN EN 175301-803 Form A)	<b>36</b> 6 ft Intergral Cable
	<b>7</b> Mini-Hirschmann (DIN EN 175301-803 Form C)	<b>25</b> M12 x 1 4-pin	

<b>OPTIONS</b>	<b>ORF</b> Threaded Orifice (.3mm)
----------------	------------------------------------

**Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.**