

## ORDERING INFORMATION

<b>SERIES</b>	<b>600</b>									
<b>PRESSURE</b>	0 psig to 15 psig	<b>15</b>	0 psig to 200 psig	<b>200</b>	0 psig to 1000 psig	<b>1000</b>	0 psig to 7500 psig	<b>7500</b>	0 psia to 60 psia	<b>60A</b>
	0 psig to 30 psig	<b>30</b>	0 psig to 300 psig	<b>300</b>	0 psig to 1500 psig	<b>1500</b>	0 psig to 10000 psig	<b>10000</b>	0 psia to 100 psia	<b>100A</b>
	0 psig to 60 psig	<b>60</b>	0 psig to 500 psig	<b>500</b>	0 psig to 2000 psig	<b>2000</b>	0 psig to 15000 psig	<b>15000</b>	0 psia to 150 psia	<b>150A</b>
	0 psig to 100 psig	<b>100</b>	0 psig to 600 psig	<b>600</b>	0 psig to 3000 psig	<b>3000</b>	0 psia to 15 psia	<b>15A</b>		
	0 psig to 150 psig	<b>150</b>	0 psig to 750 psig	<b>750</b>	0 psig to 5000 psig	<b>5000</b>	0 psia to 30 psia	<b>30A</b>		

psig = Gauge Pressure    psia= Absolute Pressure    Other ranges available on special request

<b>ACCURACY</b>	<b>1</b> ± 0.5 % Full Scale (Best Fit Straight Line)			
<b>OUTPUT SIGNALS</b>	<b>1</b> 4 mA to 20 mA, 2-wire	<b>3</b> 1 Vdc to 5 Vdc, 3-wire	<b>4</b> 1 Vdc to 6 Vdc, 3-wire	<b>5</b> 0 Vdc to 10 Vdc, 3-wire
<b>PROCESS CONNECTIONS</b>	<b>1</b> 1/8 " NPT male*	<b>2</b> 1/4 " NPT male	*Not available on pressure ranges less than 60 psi	
<b>ELECTRICAL CONNECTIONS</b>	<b>1</b> 36 " cable (connected to option 8)	<b>8</b> Hirschmann (DIN EN 175301-803 Form A)		
	<b>14</b> Hirschmann type with 1/2 " NPT female conduit connection	<b>36</b> 36 " Integral Cable		
<b>OPTIONS</b>	<b>ORF</b> SS Threaded Orifice			

**Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.**