

ORDERING INFORMATION

	SERIES 625 Stainless steel threaded connection	SERIES 626S 316 stainless steel flush diaphragm	SERIES 626H Hastelloy flush diaphragm
PRESSURE RANGES	0 inH ₂ O to 50 inH ₂ O 50 IN	0 psig to 2 psig 2	0 psig to 5000 psig 5000
	0 inH ₂ O to 100 inH ₂ O 100 IN	0 psig to 3 psig 3	0 psig to 8000 psig 8000
	-30 inHg to 0 psig 30V	0 psig to 5 psig 5	0 psig to 10000 psig 10000
	-30 inHg to 30 psig 30/30	0 psig to 15 psig 15	0 psig to 15000 psig 15000
	-30 inHg to 60 psig 30/60	0 psig to 30 psig 30	0 psig to 25000 psig 25000
	-30 inHg to 100 psig 30/100	0 psig to 50 psig 50	0 psig to 40000 psig 40000
	-30 inHg to 150 psig 30/150	0 psig to 100 psig 100	0 psig to 60000 psig 60000
	-30 inHg to 200 psig 30/200	0 psig to 150 psig 150	
psig = Gauge Pressure psia = Absolute Pressure Other ranges available on special request NOTE: Series 626 is available for pressure ranges up to 0 psig to 8000 psig			
ACCURACY	1 ±0.25 % Full Scale (Best Fit Straight Line)		2 ±0.125 % Full Scale (Best Fit Straight Line)
OUTPUT SIGNALS	1 4 mA to 20 mA, 2-wire		
PROCESS CONNECTIONS	2 1/4 " NPT male	3 7/16 "-20 UNF SAE #4 male	8 1/2 " NPT male
	11 G1/2B male flush (model 626 only) (pressure ranges 0 psig to 30 psig and higher)	13 G1B male flush (model 626 only) (pressure ranges less than 0 psig to 30 psig)	
ELECTRICAL CONNECTIONS	1 36 " cable (connected to option 8)	25 M12x1 4-pin IP67	36 Integral cable 36" - IP67
	3 6-pin bendix - IP65		
	8 Hirschmann (DIN EN 175301-803 Form A)		
	14 Hirschmann connector 1/2 " NPT conduit - IP65		
OPTIONS	ORF Threaded Orifice (model 625 only)		

Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.