

## ORDERING INFORMATION

<b>SERIES</b>	<b>630C</b> (copper alloy wetted parts)					
<b>PRESSURE RANGES</b>	-30 inHg to 0 psig	<b>30vac</b>	-30 inHg to 200 psig	<b>30/200</b>	0 psig to 30 psig	<b>30</b>
	-30 inHg to 15 psig	<b>30/15</b>	-30 inHg to 300 psig	<b>30/300</b>	0 psig to 60 psig	<b>60</b>
	-30 inHg to 30 psig	<b>30/30</b>	0 psig to 2 psig	<b>2</b>	0 psig to 100 psig	<b>100</b>
	-30 inHg to 60 psig	<b>30/60</b>	0 psig to 5 psig	<b>5</b>	0 psig to 150 psig	<b>150</b>
	-30 inHg to 100 psig	<b>30/100</b>	0 psig to 10 psig	<b>10</b>	0 psig to 200 psig	<b>200</b>
	-30 inHg to 150 psig	<b>30/150</b>	0 psig to 15 psig	<b>15</b>	0 psig to 300 psig	<b>300</b>
	psig = Gauge Pressure		Other ranges available on special request			
<b>ACCURACY</b>	<b>1</b> ±1.0 % Full Scale (Full Scale Typical)					
<b>OUTPUT SIGNALS</b>	<b>2</b> 0 Vdc to 5 Vdc, 3-wire	<b>5</b> 0 Vdc to 10 Vdc, 3-wire	<b>13</b> .5 Vdc to 4.5 Vdc ratio-metric to power supply, 3-wire			
	<b>3</b> 1 Vdc to 5 Vdc, 3-wire	Other outputs available on special request				
<b>PROCESS CONNECTIONS</b>	<b>1</b> 1/8" NPT male	<b>2</b> 1/4" NPT male				
<b>ELECTRICAL CONNECTIONS</b>	<b>1</b> 6' cable	<b>25</b> M12 x 1 4-pin				
<b>OPTIONS</b>	<b>ORF</b> Threaded Orifice					

Please consult your local NOSHOK Distributor or NOSHOK, Inc. for minimum quantity requirements and delivery information.