

ORDERING INFORMATION

SERIES	755 Stainless steel threaded		756S 316 SS flush			756H Hastelloy C4 flush		
PRESSURE RANGES	0 psig to 5 psig	5	0 psig to 250 psig	250	0 psig to 3000 psig	3000	0 psia to 5 psia	5A
	0 psig to 25 psig	25	0 psig to 500 psig	500	0 psig to 7500 psig	7500	0 psia to 25 psia	25A
	0 psig to 100 psig	100	0 psig to 1500 psig	1500	0 psig to 15000 psig	15000	0 psia to 100 psia	100A
							0 psia to 250 psia	250A
	psig = Gauge Pressure		psia = Absolute Pressure					
ACCURACY	1 ±0.05 % Full Scale (Best Fit Straight Line)							
OUTPUT SIGNAL	1 4 mA to 20 mA, 2-wire							
PROCESS CONNECTION	2 1/4 " NPT male			8 1/2 " NPT male				
	11 G1/2B male flush (model 756 only) (pressure ranges 0 psig to 100 psig and higher)			13 G1B male flush (model 756 only) (pressure ranges less than 0 psig to 100 psig)				
ELECTRICAL CONNECTION	24 Cable gland M20x1.5 with internal terminal block, accepts cable diameter from .25 " to .5 "							
OPTION	ORF Threaded orifice (Model 755 Only)							

Specify actual calibration, otherwise transmitter will be set for full scale range

Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.