

ORDERING INFORMATION

SERIES 800/810	800 Stainless Steel Housing	810 Black Anodized Aluminum Housing				
SWITCH FUNCTION	1 2 N.O. or 2 N.C. (PNP or NPN)	2 1 N.O. or 1 N.C. (PNP or NPN) with 4 mA to 20 mA Analog Output				
	3 1 N.O. or 1 N.C. (PNP or NPN) with 0 Vdc to 10 Vdc Analog Output	4 2 N.O. or 2 N.C. (NPN) with 4 mA to 20 mA Analog Output				
PROCESS CONNECTIONS	2 1/4 " NPT Male	5 1/4 " NPT Female	8 1/2 " NPT Male	10 G 1/4 B Male		
	11 G1/2B Male	19 G1/4B Female	45 7/16-20 UNF SAE #4 (Non-Adjustable)			
SWITCH ADJUSTMENT RANGE (MAXIMUM WORK PRESSURE)	-14.5 psig to 30 psig	14.5/30	0 psig to 145 psig	145	0 psig to 3750 psig	3750
	-14.5 psig to 75 psig	14.5/75	0 psig to 300 psig	300	0 psig to 6000 psig	6000
	-14.5 psig to 145 psig	14.5/145	0 psig to 750 psig	750	0 psig to 9000 psig	9000
	0 psig to 30 psig	30	0 psig to 1450 psig	1450		
	0 psig to 75 psig	75	0 psig to 2400 psig	2400		
ELECTRICAL CONNECTIONS	2 M12 x 1 (4-Pin)	3 M12 x 1 (5-Pin), 2 switch and analog output				
OPTIONS	ORF Threaded Orifice	RB Rotatable Base	EH Enhanced Software ¹			

¹Includes Minimum/Maximum Value Memory, Output Dampening, Switching Time Delay