

ORDERING INFORMATION

SERIES 21	210							
CLAMP SIZE	42 1 1/8 Inch Flange							
SEAL FILL FLUID	4 FFL77 White Oil (Other Fill Fluids Available - Please Consult Factory)							
TRANSMITTER	615 Series 615 Transmitter							
ACCURACY	1 ±0.25% Full Scale (Best fit straight line)				2 ±0.125% (Best fit straight line)			
PRESSURE RANGE	0 psig to 1000 psig	73	0 psig to 2000 psig	79	0 psig to 5000 psig	85	0 psig to 10000 psig	91
	0 psig to 1500 psig	76	0 psig to 3000 psig	82	0 psig to 6000 psig	88	0 psig to 15000 psig	94
OUTPUT SIGNAL	1 4 mA to 20 mA, 2-wire			3 1 Vdc to 5 Vdc, 3-wire			5 0 Vdc to 10 Vdc, 3-wire	
	2 0 Vdc to 5 Vdc, 3-wire			4 1 Vdc to 6 Vdc, 3-wire			6 1 Vdc to 11 Vdc, 3-wire	
ELECTRICAL CONNECTION	1 36 " cable attached to Hirschmann				14 Hirschmann connection with ISO 4400 1/2 inch NPT conduit			
	3 6-Pin Bendix				25 M12 X 1 4-pin			
	8 Hirschmann (DIN EN 175301-803 Form A)				36 Integral 36 " cable			