

ORDERING INFORMATION

TYPE	10 (2,000 psi)	10H (5,000 psi)		
INSTRUMENT CONNECTION SIZES	02 1/4" NPT	04 1/2" NPT		
UPPER HOUSING MATERIALS	C Carbon steel	S 316 Stainless steel		
DIAPHRAGM MATERIALS	A Tantalum	M Monel 400	S 316 Stainless steel ²	U Titanium Grade 4
	H Hastelloy C – 276	N Inconel 600	T PTFE ^{1 4}	V FKM ^{1 3}
O-RING MATERIALS	B NBR	T PTFE ¹	V FKM	
PROCESS CONNECTION SIZES	02 1/4" NPT	06 3/4" NPT	10 1-1/4" NPT	
	04 1/2" NPT	08 1" NPT	12 1-1/2" NPT	
	(ASME and DIN flanges available upon request)			
LOWER HOUSING MATERIALS	C Carbon steel	M Monel 400	S 316 Stainless steel	
	H Hastelloy C-276	N Inconel 600	U Titanium	
FLUSHING CONNECTIONS	1F 1/8" NPT	2F 1/4" NPT		

¹ Not available with 10H

² NBR o-rings standard with 316SS diaphragm

³ FKM o-rings standard with FKM diaphragm

⁴ PTFE o-rings standard with all other diaphragms