

## ORDERING INFORMATION

|                         |   |  |  |  |  |  |
|-------------------------|---|--|--|--|--|--|
| <b>GAUGE SIZES</b>      | <b>25</b> 2-1/2"                          | <b>40</b> 4"                           |  |  |  |  |
| <b>CASE TYPES</b>       | <b>300</b> Brass, bottom connection       | <b>310</b> Brass, back connection      |  |  |  |  |
| <b>PRESSURE RANGES</b>  | <b>30vac</b> -30 inHg to 0 psi            | <b>30/300</b> -30 inHg to 0 to 300 psi | <b>300</b> 0 psi to 300 psi                                    | <b>3000</b> 0 psi to 3,000 psi           |  |  |
|                         | <b>30/15</b> -30 inHg to 0 to 15 psi      | <b>15</b> 0 psi to 15 psi              | <b>400</b> 0 psi to 400 psi                                    | <b>5000</b> 0 psi to 5,000 psi           |  |  |
|                         | <b>30/30</b> -30 inHg to 0 to 30 psi      | <b>30</b> 0 psi to 30 psi              | <b>600</b> 0 psi to 600 psi                                    | <b>6000</b> 0 psi to 6,000 psi           |  |  |
|                         | <b>30/60</b> -30 inHg to 0 to 60 psi      | <b>60</b> 0 psi to 60 psi              | <b>800</b> 0 psi to 800 psi                                    | <b>7500</b> 0 psi to 7,500 psi           |  |  |
|                         | <b>30/100</b> -30 inHg to 0 to 100 psi    | <b>100</b> 0 psi to 100 psi            | <b>1000</b> 0 psi to 1,000 psi                                 | <b>10000</b> 0 psi to 10,000 psi         |  |  |
|                         | <b>30/160</b> -30 inHg to 0 to 160 psi    | <b>160</b> 0 psi to 160 psi            | <b>1500</b> 0 psi to 1,500 psi                                 | <b>15000</b> 0 psi to 15,000 psi         |  |  |
|                         | <b>30/200</b> -30 inHg to 0 to 200 psi    | <b>200</b> 0 psi to 200 psi            | <b>2000</b> 0 psi to 2,000 psi                                 |  |  |  |
| <b>SCALE OPTIONS</b>    | <b>psi</b> psi single scale               | <b>psi/kPa</b> psi/kPa dual scale      | <b>psi/kg/cm<sup>2</sup></b> psi/kg/cm <sup>2</sup> dual scale | <b>psi/bar</b> psi/bar dual scale        |  |  |
| <b>CONNECTION SIZES</b> | <b>1/4</b> 1/4" NPT                       | <b>1/2</b> 1/2" NPT                    | <b>SST</b> SAE J1926-3:7/16-20 Adjustable                      |  |  |  |
| <b>OPTIONS</b>          | <b>CFF</b> Chrome Front Flange            | <b>RF</b> Rear Flange                  | <b>GLO</b> Glass Lens Overlay                                  | <b>ST</b> Stainless Steel Tagging        |  |  |
|                         | <b>CFFN</b> Chrome Front Flange w/o holes | <b>CCR</b> Chrome Cover Ring           | <b>SGO</b> Safety Glass Overlay                                | <b>BT3</b> Brass Threaded Orifice 0.3 mm |  |  |
|                         | <b>BFF</b> Brass Front Flange             | <b>CBU</b> Chrome Bezel & U-Clamp      | <b>AR</b> Adapter Ring   | <b>BT4</b> Brass Threaded Orifice 0.4 mm |  |  |
|                         | <b>BLFF</b> Black Front Flange            | <b>MIP</b> Maximum Indicating Pointer  | <b>LM</b> Laser Marking  | <b>BT8</b> Brass Threaded Orifice 0.8 mm |  |  |
|                         | <b>SSRF</b> 304SS Rear Flange             | <b>LL</b> Polycarbonate Lens           |  |  |  |  |

**Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.**

**NOTE:** Refer to 300 Series Options & Accessories chart on page 51 for availability by part number.