

ORDERING INFORMATION

GAUGE SIZE	15 1-1/2"	25 2-1/2"	40 4" *	60 6" *
CASE TYPES	400 All SS, dry/fillable, bottom connection 401 All SS, dry, bottom connection 402 SS case, solid front, dry, bottom connection	410 All SS, dry/fillable, back connection 411 All SS, dry, back connection 500 SS case, liquid filled, bottom connection	502 SS case, solid front, liquid filled, bottom connection 510 SS case, liquid filled, back connection	
PRESSURE RANGES	30vac -30 inHg to 0 psi *** 30/15 -30 inHg to 0 psi to 15 psi *** 30/30 -30 inHg to 0 psi to 30 psi *** 30/60 -30 inHg to 0 psi to 60 psi *** 30/100 -30 inHg to 0 psi to 100 psi *** 30/160 -30 inHg to 0 psi to 160 psi *** 30/200 -30 inHg to 0 psi to 200 psi *** 30/300 -30 inHg to 0 psi to 300 psi *** 15 0 psi to 15 psi	30 0 psi to 30 psi 60 0 psi to 60 psi 100 0 psi to 100 psi 160 0 psi to 160 psi 200 0 psi to 200 psi 300 0 psi to 300 psi 400 0 psi to 400 psi 600 0 psi to 600 psi 800 0 psi to 800 psi	1000 0 psi to 1,000 psi 1500 0 psi to 1,500 psi 2000 0 psi to 2,000 psi 3000 0 psi to 3,000 psi 5000 0 psi to 5,000 psi 6000 0 psi to 6,000 psi 10000 0 psi to 10,000 psi 15000 0 psi to 15,000 psi 20000 0 psi to 20,000 psi **	
SCALE OPTIONS	psi psi single scale psi/kPa psi/kPa dual scale	psi/kg/cm² psi/kg/cm ² dual scale psi/bar psi/bar dual scale		
CONNECTION SIZES	1/8 1/8" NPT 1/4 1/4" NPT	1/2 1/2" NPT 9/16-18 9/16"-18 UNF 2B high pressure cone	SST SAE J1926-3:7/16-20 Adjustable	
OPTIONS	SSFF 304SS Front Flange SSRF 304SS Rear Flange SSBU Stainless Steel Bezel & U-Clamp SPMC 304SS Panel Mount Clamp PMC Steel Panel Mount Clamp	SSFR 304SS Flange Ring AP Adjustable Pointer SG Safety Glass Lens MIP Maximum Indicating Pointer SP Red Set Pointer	LM Laser Marking ST Stainless Steel Tagging ST5 Stainless Steel Threaded Orifice 0.5 mm ST8 Stainless Steel Threaded Orifice 0.8 mm	

Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.

NOTE: Refer to 400/500 Series options & Accessories chart on page 52 for availability by part number.

* On 40-400, 40-410, 40-500, 40-510, 60-400, 60-410, 60-500, and 60-510 models with 20,000 psi, the accuracy is $\pm 1.5\%$ or 1.6%

** 4" model only available with solid front case types

*** Ammonia gauges are available in these ranges. To order, add " – AMMONIA" at the end of the part number.