

## ORDERING INFORMATION

<b>GAUGE SIZE</b>	<b>40</b> 4"	<b>60</b> 6" *	
<b>CASE TYPES</b>	<b>402</b> Dry, bottom connection	<b>412</b> Dry, lower back connection	<b>502</b> Liquid filled, bottom connection
<b>PRESSURE RANGES</b>	<b>30000</b> 0 psi to 30,000 psi	<b>50000</b> 0 psi to 50,000 psi	<b>75000</b> 0 psi to 75,000 psi
	<b>40000</b> 0 psi to 40,000 psi	<b>60000</b> 0 psi to 60,000 psi	<b>85000</b> 0 psi to 85,000 psi **
<b>SCALE OPTIONS</b>	<b>psi</b> psi single scale	<b>psi/kg/cm<sup>2</sup></b> psi/kg/cm <sup>2</sup> dual scale	
	<b>psi/kPa</b> psi/kPa dual scale	<b>psi/bar</b> psi/bar dual scale	
<b>CONNECTION SIZES ***</b>	<b>9/16-18</b> 9/16"-18 UNF 2B high pressure cone - Female	<b>9/16-HPM</b> 9/16"-18 UNF 2A left hand thread - Male	
<b>OPTIONS</b>	<b>BRSP</b> Bayonet Ring Adjustable Set Pointer	<b>SL</b> Silicone Fill	<b>ST</b> Stainless Steel Tagging
	<b>LM</b> Laser Marking	<b>SP</b> Red Set Pointer	<b>IA</b> Increased Accuracy
	<b>MIP</b> Maximum Indicating Pointer	<b>SSFF</b> 304SS Front Flange	

**Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.**

\* Bottom connection only.

\*\* Only available on 60-402 and 60-502 models, with  $\pm 1.6\%$  accuracy.

\*\*\* Additional process connection sizes available, consult factory.