

ORDERING INFORMATION

GAUGE SIZES	45 4-1/2"				
CASE TYPES	640 Brass, dry, bottom connection		660 Brass, liquid filled, bottom connection		
	740 SS, dry, bottom connection		760 SS, liquid filled, bottom connection		
PRESSURE RANGES	30vac -30 inHg to 0 psi	30/300 -30 inHg to 0 to 300 psi	300 0 psi to 300 psi	3000 0 psi to 3,000 psi	
	30/15 -30 inHg to 0 to 15 psi	15 0 psi to 15 psi	400 0 psi to 400 psi	5000 0 psi to 5,000 psi	
	30/30 -30 inHg to 0 to 30 psi	30 0 psi to 30 psi	600 0 psi to 600 psi	6000 0 psi to 6,000 psi	
	30/60 -30 inHg to 0 to 60 psi	60 0 psi to 60 psi	800 0 psi to 800 psi	10000 0 psi to 10,000 psi	
	30/100 -30 inHg to 0 to 100 psi	100 0 psi to 100 psi	1000 0 psi to 1,000 psi	15000 0 psi to 15,000 psi	
	30/160 -30 inHg to 0 to 160 psi	160 0 psi to 160 psi	1500 0 psi to 1,500 psi		
	30/200 -30 inHg to 0 to 200 psi	200 0 psi to 200 psi	2000 0 psi to 2,000 psi		
SCALE OPTIONS	psi psi single scale	psi/kg/cm² psi/kg/cm ² dual scale	psi/bar psi/bar dual scale		
CONNECTION SIZES	1/4 1/4" NPT		1/2 1/2" NPT		
OPTIONS	SG Safety Glass Lens	CPMR Uninstalled Chrome Panel Mount Ring	BP3 Brass Press Fit Orifice 0.3 mm		
	GL Glass Lens	OS Overload Stop	BT3 Brass Threaded Orifice 0.3 mm		
	MIP Maximum Indicating Pointer	LM Laser Marking	ST8 316SS Threaded Orifice 0.8 mm		
	BPMR Uninstalled Black Panel Mount Ring	ST Stainless Steel Tagging			

Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.

NOTE: Refer to 600/700 Series Options & Accessories chart on page 52 for availability by part number.