

ORDERING INFORMATION

GAUGE SIZES & SERIES	25 - 10 2-1/2"	45 - 10 4-1/2"	60 - 10 6"
CONNECTION LOCATIONS	0 Bottom	1 Back	2 Side
CONNECTION SIZE	2 1/4" NPT female	9 7/16-20 female (Back only)	
PRESSURE RANGES *	P5 0 psid to 5 psid	P20 0 psid to 20 psid	P50 0 psid to 50 psid P100 0 psid to 100 psid
	P10 0 psid to 10 psid	P25 0 psid to 25 psid	P60 0 psid to 60 psid P110 0 psid to 110 psid
	P15 0 psid to 15 psid	P30 0 psid to 30 psid	P75 0 psid to 75 psid
SENSOR HOUSING MATERIALS	A Aluminum (3,000 max working pressure)		S 316L Stainless Steel (6,000 max working pressure)
O-RING & DIAPHRAGM MATERIALS	1 PTFE	3 NBR	
	2 FKM	4 EPDM	
CASE MATERIALS	A Aluminum (4-1/2" only)	P Engineered plastic	
LENSES	1 Shatter-resistant acrylic	2 Safety glass **	3 Maximum indicating pointer (MIP) ***
FILL FLUID (optional)	GY Glycerin	SL Silicone †	
SWITCH OR TRANSMITTER TYPE & HOUSING	1 Single switch, flying leads with grommet wire seal	5 Single switch with Hirschman electrical connection	
	2 Dual switch, flying leads with grommet wire seal	6 Dual switch with Hirschman electrical connection	
	3 Single switch, flying leads with 1/4" female NPT, NEMA 4X	7 4-20 mA transmitter in NEMA 4x IP65 plastic enclosure with terminal strip (1/2" female NPT conduit connection)	
	4 Dual switch, flying leads with 1/4" female NPT, NEMA 4X		
OPTIONS	MH (2) 1/4-20 Mounting Holes	RP Reversed Ports	
	MK5-CS Pipe Mounting Kit, Steel	ST Stainless Steel Tagging	
	MK5-SS Pipe Mounting Kit, Stainless Steel	WMK Wall Mounting Kit	

Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.

* Other ranges and scales available on request.

** Only available with dry, 4-1/2" gauge size with Aluminum case.

*** Available with dry gauge only, 2-1/2" and 4-1/2" gauge sizes only.

† Optional Silicone filling available with 2-1/2" and 6" gauge case sizes, and 4-1/2" gauge case size with Aluminum case and standard shatter-resistant acrylic lens only.