

## ORDERING INFORMATION

<b>GAUGE SIZES &amp; SERIES</b>	<b>25 - 11</b> 2-1/2"	<b>45 - 11</b> 4-1/2"	<b>60 - 11</b> 6"
<b>CONNECTION LOCATIONS</b>	<b>0</b> Dual top & bottom ***	<b>1</b> Back	<b>2</b> Side <b>3</b> Bottom
<b>CONNECTION SIZE</b>	<b>2</b> 1/4" NPT female	<b>9</b> 7/16-20 female (Back or side only)	
<b>PRESSURE RANGES*</b>	<b>W20</b> 0 inH <sub>2</sub> O to 20 inH <sub>2</sub> O	<b>W75</b> 0 inH <sub>2</sub> O to 75 inH <sub>2</sub> O	<b>W400</b> 0 inH <sub>2</sub> O to 400 inH <sub>2</sub> O
	<b>W25</b> 0 inH <sub>2</sub> O to 25 inH <sub>2</sub> O	<b>W100</b> 0 inH <sub>2</sub> O to 100 inH <sub>2</sub> O	<b>P5</b> 0 psid to 5 psid
	<b>W30</b> 0 inH <sub>2</sub> O to 30 inH <sub>2</sub> O	<b>W135</b> 0 inH <sub>2</sub> O to 135 inH <sub>2</sub> O	<b>P10</b> 0 psid to 10 psid
	<b>W40</b> 0 inH <sub>2</sub> O to 40 inH <sub>2</sub> O	<b>W150</b> 0 inH <sub>2</sub> O to 150 inH <sub>2</sub> O	<b>P15</b> 0 psid to 15 psid
	<b>W50</b> 0 inH <sub>2</sub> O to 50 inH <sub>2</sub> O	<b>W200</b> 0 inH <sub>2</sub> O to 200 inH <sub>2</sub> O	<b>P20</b> 0 psid to 20 psid
	<b>W60</b> 0 inH <sub>2</sub> O to 60 inH <sub>2</sub> O	<b>W300</b> 0 inH <sub>2</sub> O to 300 inH <sub>2</sub> O	<b>P25</b> 0 psid to 25 psid
<b>SENSOR HOUSING MATERIALS</b>	<b>A</b> Aluminum, black	<b>B</b> Brass	<b>S</b> 316L Stainless Steel
<b>O-RING &amp; DIAPHRAGM MATERIALS</b>	<b>2</b> FKM	<b>3</b> NBR	<b>4</b> EPDM
<b>CASE MATERIAL</b>	<b>A</b> Aluminum (4-1/2" only)	<b>P</b> Engineered plastic	
<b>LENSES</b>	<b>1</b> Shatter-resistant acrylic	<b>2</b> Safety glass**	<b>3</b> Maximum indicating pointer (MIP) †
<b>FILL FLUIDS (optional)</b>	<b>GY</b> Glycerin	<b>SL</b> Silicone ††	
<b>SWITCH OR TRANSMITTER TYPE &amp; HOUSING (OPTIONAL)</b>	<b>3</b> Single switch, NEMA 4X	<b>7</b> 4-20 mA transmitter in NEMA 4x IP65 plastic enclosure with terminal strip (1/2" female NPT conduit connection).	
	<b>4</b> Dual switch, NEMA 4X		
<b>OPTIONS</b>	<b>MH</b> (2) 1/4-20 Mounting Holes	<b>RP</b> Reversed Ports	
	<b>MK5-CS</b> Pipe Mounting Kit, Steel	<b>ST</b> Stainless Steel Tagging	
	<b>MK5-SS</b> Pipe Mounting Kit, Stainless Steel	<b>WMK</b> Wall Mounting Kit	

**Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.**

\* Other ranges and scales available on request.

\*\* Only available with dry, 4-1/2" gauge size with Aluminum case.

\*\*\* Not available with switch or transmitter option.

† Available with dry gauge only, 2-1/2" and 4-1/2" gauge sizes only.

†† Optional Silicone filling available with 2-1/2" and 6" gauge case sizes, and 4-1/2" gauge case size with Aluminum case and standard shatter-resistant acrylic lens only.