## ORDERING INFORMATION - ADDITIONAL OPTIONS

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| **PACKINGS†** | **P1** | PTFE | **P2** | Graphite** | | | | | |
| **STEM TIPS** | **T1** | Non-rotating (316 Stainless)** | **T4** | PEEK*** | **T7** | Ball (ceramic)** | **T10** | Regulating Delrin®*** |
| | **T2** | Delrin® (Acetal)*** | **T5** | Ball (440C Stainless)** | **T8** | Ball (Monel)** | **T11** | Regulating PCTFE*** |
| | **T3** | PCTFE*** | **T6** | Ball (carbide)** | **T9** | Non-rotating regulating (316 Stainless)** | **T12** | Regulating PEEK*** |
| **O-RINGS*** | **EM1** | EPDM | **KZ1** | FFKM (Kalrez® 3018 or equivalent) | **NB1** | NBR | | |
| **HANDLES** | **HL2** | 2-1/2" "T" | **HL3** | 1" Round knurled | **HL4** | 1-3/8" Phenolic | **HL5** | 1-3/4" Phenolic |

**Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.**

* Other o-ring materials available on request.
** For 3610 only.
*** For 3710 only.
† If a packing option is chosen, maximum pressure rating is 6,000 psi. Refer to the "Pressure vs. Temperature: Packing Style with Compatible Fluid" chart at the back of this catalog.

Please note that the standard o-ring in all the NOSHOK valves is FKM and the standard handles are 1-3/8" mini "T" handles (HL7).

The handle material will always match the material of the valve, unless otherwise specified. For example, the 1-3/8" mini "T" handle (HL7) on the 3710-FFC will be Steel. When only the standard configuration is needed, no additional designations are necessary. Please consult the factory for special application requests.