

ORDERING INFORMATION - ADDITIONAL OPTIONS

| | | | |
|------------------------|--|--|---|
| PACKINGS * | P1 PTFE | P2 Graphite | |
| STEM TIPS | T1 Non-rotating (316 Stainless) | T6 Ball (carbide) | T8 Ball (Monel) |
| | T5 Ball (440C Stainless) | T7 Ball (ceramic) | T9 Non-rotating regulating (316 Stainless) |
| O-RINGS ** | EM1 EPDM | KZ1 FFKM (Kalrez® 3018 or equivalent) | NB1 NBR |
| PANEL MOUNTINGS | PM1 Panel mount (1 nut) | PM2 Panel mount (2 nuts) | |
| HANDLES | HL1 1-13/16" Mini "T" | HL4 1-3/8" Phenolic | HL5 1-3/4" Phenolic |

Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.

* If a packing option is chosen, maximum pressure rating is 6,000 psi. Refer to the "Pressure vs. Temperature: Packing Style with Compatible Fluid" chart at the back of this catalog.

** Other o-ring materials available on request.

NOTE: Plugs and bleed plugs are available and can be ordered separately, see page 65.

Please note that the standard o-ring in all the NOSHOK valves is FKM and the standard handles are "T" handles (HL2).

The handle material will always match the material of the valve, unless otherwise specified. For example, the "T" handle (HL2) on the 204-MFC will be Steel. When only the standard configuration is needed, no additional designations are necessary. Please consult the factory for special application requests.