

ORDERING INFORMATION

| | | | |
|--|------------------------------------|-------------------------------------|--|
| SERIES | 200 | | |
| SWITCH FUNCTION | 1 Single changeover contact (SPDT) | | |
| PROCESS CONNECTION | 2 1/4" NPT male | | |
| SWITCH ADJUSTMENT RANGES <i>(Max. working pressure)</i> | 3/30 | 3 psig to 30 psig (870 psig) | 150/1700 150 psig to 1,700 psig (5,000 psig) |
| | 7/115 | 7 psig to 115 psig (870 psig) | 150/2300 150 psig to 2,300 psig (5,000 psig) |
| | 15/225 | 15 psig to 225 psig (870 psig) | 300/2900 300 psig to 2,900 psig (5,000 psig) |
| | 150/425 | 150 psig to 425 psig (5,000 psig) | 300/3600 300 psig to 3,600 psig (5,000 psig) |
| | 150/1150 | 150 psig to 1,150 psig (5,000 psig) | 450/4600 450 psig to 4,600 psig (5,000 psig) |
| ELECTRICAL CONNECTIONS | 4 6.3 mm Spade terminals | 36 18" Integral cable | |

Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.