

ORDERING INFORMATION

SERIES	400		
SWITCH FUNCTION	1 Single Pole Double Throw (SPDT)		
PROCESS CONNECTIONS *	2 1/4" NPT male	19 G 1/4 B female	
	5 1/4" NPT female	45 SAE J514 FIG 34B	
	10 G 1/4 B male		
SWITCH ADJUSTMENT RANGES ** <i>(Max. working pressure)</i>	3/30 3 psig to 30 psig (300 psig)	150/1700 150 psig to 1,700 psig (5,000 psig)	
	7/115 7 psig to 115 psig (300 psig)	150/2300 150 psig to 2,300 psig (5,000 psig)	
	15/225 15 psig to 225 psig (300 psig)	300/2900 300 psig to 2,900 psig (5,000 psig)	
	150/425 150 psig to 425 psig (5,000 psig)	300/3600 300 psig to 3,600 psig (5,000 psig)	
	150/1150 150 psig to 1,150 psig (5,000 psig)	450/4600 450 psig to 4,600 psig (5,000 psig)	
ELECTRICAL CONNECTIONS	1 36" Cable (connected to option 8)	8 DIN EN 175301-803 Form A	
	2 M12 x 1 (4-pin)	46 Hirschmann with LED status indicator	

Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.

* Note: Stainless Steel connection available, consult factory

** Please specify switch set point(s), rising or falling pressing, and switch hysteresis (if applicable)