

ORDERING INFORMATION

300 SERIES	25-300	2-1/2", brass case, bottom connection	25-310	2-1/2", brass case, back connection
400 SERIES	40-400	4", all stainless, bottom connection	40-410	4", all stainless, back connection
	60-400	6", all stainless, bottom connection	60-410	6", all stainless, back connection
600 SERIES	45-640	4-1/2", phenolic case/brass bottom connection		
700 SERIES	45-740	4-1/2", phenolic case/stainless bottom connection		
900 SERIES	40-901	4", stainless case, brass bottom connection	40-911	4", stainless case, brass back connection
GAUGE FILL FLUIDS	0	Dry gauge	2	-40° service
	1	Glycerin	3	Silicone
MOUNTING OPTIONS	0	None	3	Rear flange ²
	1	Chrome front flange ¹	4	Bezel & u-clamp ³
	2	Brass front flange ¹	5	Stainless steel front flange ⁴
TEMPERATURE RANGES	1	-40 °F/°C to 60 °F/°C	6	30 °F/°C to 180 °F/°C
	2	-20 °F/°C to 120 °F/°C	7	30 °F/°C to 240 °F/°C
	3	0 °F/°C to 250 °F/°C	8	30 °F/°C to 300 °F/°C
	4	0 °F/°C to 300 °F/°C	9	50 °F/°C to 350 °F/°C
	5	20 °F/°C to 220 °F/°C	10	100 °F/°C to 350 °F/°C
CAPILLARY TYPES/MATERIALS	1	Plain copper	3	Plain stainless steel
	2	Armored copper	4	Armored stainless steel
CAPILLARY LENGTH	##	Specify in feet		
BULB STYLES/MATERIALS	1	Plain copper	3	1/2" NPT union copper
	2	Plain stainless steel	4	1/2" NPT union stainless steel
BULB DIMENSIONS	1	2-5/8" x 3/8"	6	4" x 3/8"
	2	4-1/2" x 3/8"	7	9" x 3/8"
	3	8" x 3/8"	8	7-5/8" x 3/8"
	4	3-1/2" x 3/8"	15	6" x 1/2" ⁵
	5	6" x 3/8"		

Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.