

ORDERING INFORMATION

| | | | |
|--------------------------------------|--------------------------------|---|--|
| SERIES | 204 | | |
| PROCESS CONNECTIONS | 90 | E&H Universal adapter short version | 95 King Gage Standard - 6" |
| | 91 | E&H Universal adapter long version | 96 King Gage Long - 8" |
| | 92 | Anderson Negele Type SL Short | 97 Rosemount Tank Spud - 2" |
| | 93 | Anderson Negele Type SL Long - 6" | 98 Rosemount Tank Spud - 6" |
| | 94 | King Gage Short | 99 Tank Mate Medium - 6" |
| PRESSURE RANGES (Adjustable)* | 16/160 inH₂O | 16 inH ₂ O to 160 inH ₂ O (.06 psig to 6 psig) | 6/58 psig 6 psig to 58 psig (160 inH ₂ O to 1,600 inH ₂ O) |
| | 47/470 inH₂O | 47 inH ₂ O to to 470 inH ₂ O (1.7 psig to 17 psig) | |
| ACCURACIES | 1 | 0.1% of adjusted span | |
| OUTPUT SIGNALS | 1 | 4 mA to 20 mA, 2-wire | 43 4 mA to 20 mA, 2-wire and Hart® signal |
| ELECTRICAL CONNECTIONS | 25 | M12 x 1 (4-pin) | 71 PG9 Cable Gland |
| | 28 | 1/2" NPT Female | |
| OPTIONS | TC | Transparent Cover (for display) | |

Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.

*Other ranges available, consult factory