

ORDERING INFORMATION

SERIES	300			
PRESSURE RANGES	15 0 psig to 15 psig	300 0 psig to 300 psig	3000 0 psig to 3,000 psig	30A 0 psia to 30 psia
	30 0 psig to 30 psig	500 0 psig to 500 psig	5000 0 psig to 5,000 psig	60A 0 psia to 60 psia
	60 0 psig to 60 psig	750 0 psig to 750 psig	6000 0 psig to 6,000 psig	100A 0 psia to 100 psia
	100 0 psig to 100 psig	1000 0 psig to 1,000 psig	7500 0 psig to 7,500 psig	150A 0 psia to 150 psia
	150 0 psig to 150 psig	1500 0 psig to 1,500 psig	10000 0 psig to 10,000 psig	200A 0 psia to 200 psia
	200 0 psig to 200 psig	2000 0 psig to 2,000 psig	15A 0 psia to 15 psia	300A 0 psia to 300 psia
	psig = gauge pressure psia = absolute pressure Other ranges available upon request.			
ACCURACIES	1 ±0.5% full scale (BFSL)	2 ±0.25% full scale (BFSL)		
OUTPUT SIGNALS	1 4 mA to 20 mA, 2-wire	3 1 Vdc to 5 Vdc, 3-wire	13 0.5 Vdc to 4.5 Vdc, 3-wire (ratiometric)	
	2 0 Vdc to 5 Vdc, 3-wire	5 0 Vdc to 10 Vdc, 3-wire		
PROCESS CONNECTIONS	2 1/4" NPT male	10 G 1/4 B	45 SAE J514 FIG 34B (Non-Adjustable)	
	8 1/2" NPT male	11 G 1/2 B		
ELECTRICAL CONNECTIONS	1 36" cable (connected to option 8)	8 Hirschmann (DIN EN 175301-803 form A)	25 M12 x 1 (4-pin)	
	7 Mini-Hirschmann (DIN EN 175301-803 form C)	14 Hirschmann type with 1/2" NPT female conduit	36 6' Integral cable	
OPTION	ST8 Threaded Orifice (0.3 mm)			

Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.