

ORDERING INFORMATION

SERIES	621	Stainless steel threaded connection	622	316 Stainless steel flush diaphragm	622H	Hastelloy C flush diaphragm		
PRESSURE RANGES	30vac	-30 inHg to 0 psig	5	0 psig to 5 psig	300	0 psig to 300 psig	6000	0 psig to 6,000 psig
	30/30	-30 inHg to 30 psig	10	0 psig to 10 psig	500	0 psig to 500 psig	8000	0 psig to 8,000 psig
	30/60	-30 inHg to 60 psig	15	0 psig to 15 psig	1000	0 psig to 1,000 psig	10000	0 psig to 10,000 psig
	30/100	-30 inHg to 100 psig	30	0 psig to 30 psig	1500	0 psig to 1,500 psig	15000	0 psig to 15,000 psig
	30/160	-30 inHg to 160 psig	60	0 psig to 60 psig	2000	0 psig to 2,000 psig	15A	0 psia to 15 psia
	30/200	-30 inHg to 200 psig	100	0 psig to 100 psig	3000	0 psig to 3,000 psig	100A	0 psia to 100 psia
	30/300	-30 inHg to 300 psig	200	0 psig to 200 psig	5000	0 psig to 5,000 psig		
	psig = gauge pressure	psia = absolute pressure	Other ranges available on request		Note: 622 Series is available for pressure ranges up to 0 psig to 8,000 psig			
ACCURACY	1	±0.25% full scale (BFSL)						
OUTPUT SIGNALS	1	4 mA to 20 mA, 2-wire		3	1 Vdc to 5 Vdc, 3-wire, low power		31	0.5 Vdc to 4.5 Vdc 3-wire, low power
	2	0 Vdc to 5 Vdc, 3-wire		5	0 Vdc to 10 Vdc, 3-wire			
PROCESS CONNECTIONS	2	1/4" NPT male		11	G 1/2 B*			
	8	1/2" NPT male		13	G 1 B (622 Series only, <30 psig)			
ELECTRICAL CONNECTIONS	6	1/2" NPT male conduit with 6' integral cable			37	1/2" NPT male conduit with 6' flying leads with epoxy seal		
OPTIONS	ST8	Threaded Orifice (621 Series only)		20	20' Cable/lead (attached to electrical connection 6 or 37)		30	30' Cable/lead (attached to electrical connection 6 or 37)

Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.

* 622 Series only, G 1/2 B Flush (≥ 30 psig).