

ORDERING INFORMATION

SERIES	623 Stainless Steel threaded connection	624 316 Stainless Steel flush diaphragm *		
PRESSURE RANGES	30vac -30 inHg to 0 psig	30 0 psig to 30 psig	500 0 psig to 500 psig	6000 0 psig to 6,000 psig
	30/30 -30 inHg to 30 psig	60 0 psig to 60 psig	1000 0 psig to 1,000 psig	8000 0 psig to 8,000 psig
	30/60 -30 inHg to 60 psig	100 0 psig to 100 psig	1500 0 psig to 1,500 psig	10000 0 psig to 10,000 psig
	30/100 -30 inHg to 100 psig	200 0 psig to 200 psig	2000 0 psig to 2,000 psig	15000 0 psig to 15,000 psig
	15 0 psig to 15 psig	300 0 psig to 300 psig	3000 0 psig to 3,000 psig	15A 0 psia to 15 psia
			5000 0 psig to 5,000 psig	100A 0 psia to 100 psia
	psig = gauge pressure psia = absolute pressure Other ranges available on request		Note: 624 Series is available for pressure ranges up to 0 psig to 8,000 psig	
ACCURACY	1 ±0.25% full scale (BFSL)			
OUTPUT SIGNALS	1 4 mA to 20 mA, 2-wire	3 1 Vdc to 5 Vdc, 3-wire, low power	31 0.5 Vdc to 4.5 Vdc, 3-wire, low power	
PROCESS CONNECTIONS	2 1/4" NPT male	11 G 1/2 B **		
	8 1/2" NPT male	13 G 1 B (624 Series only, <30 psig)		
ELECTRICAL CONNECTION	6 1/2" NPT male conduit with 6' integral cable			
OPTION	ST8 Threaded Orifice (623 Series only)			

Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.

* Hastelloy flush diaphragm available upon request.

** 624 Series only, G 1/2 B Flush (≥ 30 psig).