

## ORDERING INFORMATION

<b>SERIES</b>	<b>800</b> 304 Stainless steel housing							
<b>SWITCH FUNCTIONS</b>	<b>1</b>	2 N.O. or N.C. (PNP or NPN)		<b>5</b>	2 N.O. or N.C. switch (PNP/NPN) with 0 Vdc to 10 Vdc 3-wire output*			
	<b>2</b>	1 N.O. or N.C. (PNP or NPN) with 4 mA to 20 mA 3-wire analog output		<b>6</b>	1 N.O. or N.C. switch (PNP/NPN) with 4 mA to 20 mA/0 Vdc to 10 Vdc 3-wire output 2**			
	<b>3</b>	1 N.O. or N.C. (PNP or NPN) with 0 Vdc to 10 Vdc 3-wire output		<b>7</b>	2 N.O. or N.C. switch (PNP/NPN) with 4 mA to 20 mA/0 Vdc to 10 Vdc 3-wire output*. **			
	<b>4</b>	2 N.O. or N.C. (PNP or NPN) with 4 mA to 20 mA analog output*						
<b>PROCESS CONNECTIONS</b>	<b>2</b>	1/4" NPT male	<b>10</b>	G 1/4 B male	<b>45</b> SAE J514 FIG B (Non-Adjustable)			
	<b>8</b>	1/2" NPT male	<b>11</b>	G 1/2 B male				
<b>ADJUSTABLE RANGES</b> <i>(Max. working pressure)</i>	<b>14.5vac</b>	-14.5 psig to 0 psig	<b>15</b>	0 psig to 15 psig	<b>1000</b>	0 psig to 1,000 psig	<b>30A</b>	0 psia to 30 psia
	<b>14.5/15</b>	-14.5 psig to 15 psig	<b>25</b>	0 psig to 25 psig	<b>1500</b>	0 psig to 1,500 psig	<b>50A</b>	0 psia to 50 psia
	<b>14.5/30</b>	-14.5 psig to 30 psig	<b>30</b>	0 psig to 30 psig	<b>2000</b>	0 psig to 2,000 psig	<b>100A</b>	0 psia to 100 psia
	<b>14.5/50</b>	-14.5 psig to 50 psig	<b>50</b>	0 psig to 50 psig	<b>3000</b>	0 psig to 3,000 psig	<b>160A</b>	0 psia to 160 psia
	<b>14.5/100</b>	-14.5 psig to 100 psig	<b>100</b>	0 psig to 100 psig	<b>5000</b>	0 psig to 5,000 psig	<b>200A</b>	0 psia to 200 psia
	<b>14.5/160</b>	-14.5 psig to 160 psig	<b>160</b>	0 psig to 160 psig	<b>7500</b>	0 psig to 7,500 psig	<b>300A</b>	0 psia to 300 psia
	<b>14.5/200</b>	-14.5 psig to 200 psig	<b>200</b>	0 psig to 200 psig	<b>10A</b>	0 psia to 10 psia		
	<b>14.5/300</b>	-14.5 psig to 300 psig	<b>300</b>	0 psig to 300 psig	<b>15A</b>	0 psia to 15 psia		
	<b>10</b>	0 psig to 10 psig	<b>500</b>	0 psig to 500 psig	<b>25A</b>	0 psia to 25 psia		
<b>ELECTRICAL CONNECTIONS</b>	<b>2</b>	M12 x 1 (4-pin)	<b>3</b>	M12 x 1 (5-pin), 2 switch and analog output				
<b>OPTIONS</b>	<b>ST8</b> Threaded Orifice							

**Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.**

\* Available only with a M12 x 1 (5-pin) connector

\*\* Can switch between 4 mA to 20 mA / 0 Vdc to 10 Vdc